

a) Hersteller manufacturer's name		AEREX HaustechnikSysteme GmbH					
b) Modellkennung (Code) manufacturer's model identifier (code)		Reco-Boxx 6000 ZXR-R / EV / WN (0040.0837)					
c) Typ typology		RVU	—	BVU	x		
		NRVU	x	UVU	—		
d) Art des eingebauten / einzubauenden Antriebes type of drive installed / intended to be installed		multi-speed	—	installed	—		
		VSD	x	intended to be instal.	—		
e) Art des WRS type of HRS		Kreislaufver. / run-around	—	anderes / other	x	keines / none	—
f) Thermischer Übertragungsgrad der WRG thermal efficiency of heat recovery		η_{t_nrvu}	83			%	
g) Nenn-Luftvolumenstrom der NWLA nominal NRVU flow rate		q_{nom}	1,67			m³/s	
h) Tatsächliche elektrische Eingangsleistung effective electric power input		p	2,679			kW	
i) Innere spezifische Ventilatorleistung internal specific fan power		SFP _{int}	1182			W/(m³/s)	
j) Anströmgeschwindigkeit face velocity		1,79			m/s		
k) Nennaußendruck nominal external pressure		$\Delta p_{s,ext}$	100			Pa	
l) Interner Druckabfall von Lüftungsbauteilen internal pressure drop ventilation components		$\Delta p_{s,int}$	323			Pa	
m) Interner Druckabfall von Nichtlüftungsbauteilen internal pressure drop non-ventilation components		$\Delta p_{s,add}$	245			Pa	
n) Statischer Wirkungsgrad Ventilator static efficiency of fans (RegulationNr. 327/2011)		η_{fan}	65,2			%	
o) Äußere Höchstlecklufrate declared maximum external leakage rate		L2 (< 1%)			%		
Innere Höchstlecklufrate declared maximum internal leakage rate		1			%		
p) Energetische Eigenschaften der Filter energy performance of the filters		—			kWh/a		
q) Beschreibung optische Filterwarnanzeige description of visual filter warning		LED - replace the filter continous-ly to preserve the device properties					
r) Gehäuse-Schallleistungspegel casing sound power level		L _{WA..}	66			dB[A]	
s) Internetadresse für Anweisungen zur Zerlegung/Demontage internet address for disassembly instructions		www.aerex.de					